



STYLE 5765-YE

SPILL PAL 5765-YE

**Features:**

This is the easiest to use and the most affordable / convenient hazardous material storage product. It provides incidental spill control during temporary storage of drums, machine parts, tanks and generators. Available in 6 configurations and custom sizes of 1 / 2 / 4 / 6 / 8 drums Durable & Reusable, folds up and stores easily to maximize your work floor & shelf space

**Approvals:**

EPA / SPCC / NPDES



POLY OVERPACK / SALVAGE DRUM

POLY OVERPACK / SALVAGE DRUM

**Features:**

Salvage Drums is versatile unit that can directly contain solids and sludge's with security. With a 1/2 turn lid, these ergonomically designed units allow for easy access, unlike competing "hoop-ring designs." These are available for 20 / 30 / 50 / 95 / 110 gallon Salvage Drums.

**Approvals:**

UN 1H2/X75/S, DOT 49CFR 173.3(c), EPA, SPCC and NPDES



SPILL KITS

SPILL KITS

**Features:**

Basic spill kits contents: Pads / Socks / Disposal Bags / Ties / Nitrile Gloves / Safety Goggles Available in 5, 20, 30, 50, 65 and 95 gallons Available in Oil only, Universal and Hazmat type



STYLE 7302-BK

DUAL CYLINDER DOLLY-7302-BK

**Features:**

Accommodates any two cylinders, each up to 12" in diameter including class 300 SCF industrial gas cylinders and No.5 acetylene cylinders  
Load Bearing Capacity UDL: 500lbs / 227kg



STYLE 6000(5400-YE-D)

POLY-SLIM-LINE™ 6000 (5400-YE-D)

**Features:**

Secondary containment system  
Load Bearing Capacity UDL: 6000lbs / 2722kg  
Sump Capacity: 66gals / 250liters

**Approvals:**

Meets EPA 40 CFR 264.175, SPCC and NPDES regulations



STYLE 5300-YE

POLY DOLLY® -5300-YE

**Features:**

Transports 55 gallon drums with ease, tilts to become an efficient self-dispensing station and acts as its own secondary containment unit  
Tough polyethylene construction, cannot rust or corrode  
Hold up to 600 lbs to cover most applications  
Load Bearing Capacity UDL: 600lbs / 273kg  
Sump Capacity: 80gal / 303kg

**Approvals:**

Meets EPA 40 CFR 264.175, SPCC and NPDES regulations